

# CONCRETE SEALER

## SATIN GLOSS

www.saniten.ca

February 15, 2014

*Water based acrylic/urethane sealer for concrete surfaces leaving a satin gloss finish.*

### DIRECTIONS

#### SURFACE PREPARATION

**New installation:** Wait concrete curing time of 28 days before sealing it.

**Existing surface:** The sealer can be applied over a solvent based sealer but the surface must be lightly sanded or scuffed before. Use SANITEN's black scuff pad TP250. Once sanded, deep clean the surface with SANITEN Heavy Duty Cleaner PD1010. Rinse and let dry 24 hours before sealing it.

#### APPLICATION

With a paint brush or a paint roller, apply a thin coat of sealer. Spread the sealer slowly to avoid formation of air bubbles. Let the surface dry completely (4 to 6 hours) before applying another coat. We recommend the application of 2 coats. Light circulation after 24 hours. Normal circulation after 72 hours. Curing time: 28 days.

### CAUTION & LIMITATIONS

MAY IRRITATE EYES Do not get in eyes. Do not get on skin or clothing. Keep out of reach of children.

#### **FIRST AID TREATMENT**

Contains urethane and acrylic emulsions. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 20 minutes with eye lids open. If on skin, rinse well with water.

### PACKAGING

946ml - 12 per case  
4 litres - 4 per case  
20 litres - pail

### COVERAGE

946ml covers approximately 20m<sup>2</sup> (200ft<sup>2</sup>).

### HANDLING & STORAGE

Avoid from freezing.  
Store in original container, well closed in a dry area at room temperature.  
Shelf life: 2 years  
Do not put excess sealer in the garbage.  
Dispose in an appropriate waste site.

### TECHNICAL SUPPORT

Refer to the web site [www.saniten.ca](http://www.saniten.ca) or call 1-877-726-5836.

Test first the product on a small and adequate area.

Protect the neighboring area against unexpected contact with the product. Product should be used at room temperature, between 10 and 25°C.



Product code: PS1295

N.B. All information here above is accurate. But having no control over the conditions of utilization of the product, we cannot assume any responsibility, legal or other, in regards of the results and/or any prejudice derived from.

### RECOMMENDED SURFACES:

- Concrete & stamped concrete
- Floors
- Residential, commercial and institutional applications
- Interior use

### CHARACTERISTICS:

- Gloss rating: 30 to 35
- Protects against household dirt and stains
- Provides water and oil repellent protection
- Faint odor
- Can be dyed
- Doesn't contain ammonia
- Good leveling
- Dries quickly
- NMP free
- NPEO free

### PERFORMANCE:

- Meets chemical resistance test CAN/CGSB-25.20-95 for floor surface sealers (Type 1).
- Meets Static Coefficient of Friction test ASTM D2047 for polished-coated floor surfaces.

### ENVIRONMENTAL DATA:

- Low VOC: <250gr / liter
- Biodegradable. In conformity with OCDE 301 E rule
- Designed to meet ÉcoLogo specifications

### REMOVER:

- Heavy Duty Cleaner PD1010
- Urethane Remover PD2020

### MAINTENANCE:

- Neutral Floor Cleaner N300
- Multi-Surface Cleaner BR110
- Industrial Cleaner PN320